

Visual UpTime Select Rack-mounted Single-Processor Server

Revision Date: July 12, 2006

These are the minimum specifications for a new rack-mounted single-processor server for Visual UpTime Select. The rack itself is not included. The specification is intended for new customer purchases.

Monitor: 15" analog flat panel

Computer: Dell 1950 server or equivalent with Intel dual-core Xeon 3.0 GHz single processor or higher with 2MB cache minimum. Redundant power supply with Y-cord included.

Footprint: rack. Sliding Rapid/Versa Rails (Universal) included. No Bezel.

Mouse: USB, 2-button, Windows compatible (e.g., Logitech or Microsoft)

Keyboard: standard

Memory (RAM): 1GB minimum

CD-ROM: 24X CD-RW/DVD minimum

Modem: Internal 56kbps modem not required. Customer provides own access..

Disk space: Dual 146GB SAS drives, 10K rpm minimum, attached to integrated PERC5/i RAID 1 (mirrored). Backplane: 1x2 for 3.5" drives.

Floppy disk: none

Tape backup: none

Operating system: Windows Server 2003 R2 Standard Edition with 5 Client Access Licenses.

Ethernet card: internal dual-port Gigabit NIC

Maintenance: 3 year, next business day parts and labor, no software support. No installation support.

Other components: SQL Server 2005 Standard Edition with 5 CALs is required, but should not be included in a quote by Dell. Visual obtains them in bulk through a software supplier. System is customer-installed. SQL Server 2000 will be installed using the license from SQL Server 2005.