

## Visual UpTime Select Single-Processor Server

**Revision Date:** July 12, 2006

These are the minimum specifications for a new single-processor server for Visual UpTime Select. The specification is intended for new customer purchases.

**Monitor:** 15" analog flat panel

**Computer:** Dell 2900 server or equivalent with Intel dual-core Xeon 3.0 GHz single processor or higher with 2MB cache minimum. Redundant power supply included with Y cord.

**Footprint:** Tower, with Bezel.

**Mouse:** USB, 2-button, Windows compatible, with scroll (e.g., Logitech or Microsoft)

**Keyboard:** standard keyboard

**Memory (RAM):** 1GB minimum

**CD-ROM:** 48X IDE CD-RW/DVD ROM combination drive

**Modem:** Internal 56kbps PCI

**Disk space:** Dual 146GB SAS drives, 10K rpm minimum, attached to integrated PERC-5/Si RAID 1 (mirrored). Include PERC user documentation.

**Floppy disk:** none

**Tape backup:** PowerVault 100T, DAT72, 36/72GB, Internal Tape Backup Unit w controller

**Operating system:** Windows Server 2003 Standard Edition R2 with 5 Client Access Licenses.

**Ethernet card:** internal dual-port Gigabit NIC (10/100/1000) with TCP/IP offload enabled for Microsoft OS.

**Maintenance:** 3 year, next business day parts and labor, no software support, no installation support

**Other components:** SQL Server 2005 Standard Edition with 5 CALs is required, but should not be included in a quote by Dell. Visual obtains them in bulk through a software

supplier. System is customer-installed. SQL Server 2000 will be installed using the license from SQL Server 2005.